



Roca

Onyx

Onyx


The Onyx series gathers light with warm nuances of waves that run smoothly over the surface of this porcelain tile, which create a feeling of spaciousness and luminosity.



Onyx White 24"x48" R PO

Glazed & Polished Porcelain

12"x24" R - 24"x48" R



12"x24" R 30x60 cm
24"x48" R 60x120 cm



White



12"x24" R PO
 GFWHONX-1224PO



12"x24" R UP
 GFWHONX-1224



24"x48" R PO
 GFWHONX-2448PO

Technical Specifications

CHARACTERISTICS	STANDARD	DECLARED ASTM	
		Polished	Unpolished
Water Absorption	C373	<=0.5%	<=0.5%
Break Strength	C648	Min. 290	Min. 290
Scratch Hardness	MOH's Scale	3	5
Chemical Resistance	C650	Unaffected	Unaffected
Frost Resistance	C1026	Resistant	Resistant
Group	See FAQ's	3	3
Deep Abrasion - Unglazed Tiles	C1243	Pass	Pass
PEI - Glazed Tiles	C1027	3	3
Minimum Bond Strength (PSI)	C482	165	165
Dynamic Coefficient of Friction (DCOF)	A137.1	>=0.42	<=0.42
Shade and Texture Rating	CTDA "V"	V3	V3
Facial Dimensions	C499	Pass	Pass
Range of Thickness	C499	Pass	Pass
Warping	C485	Pass	Pass
Wedging	C502	Pass	Pass

Packaging Info

Size	SF per carton	PC per carton
12"x24"	15.50	8
24"x48"	15.50	2