

Lotus + 20mil Glue Down

TECHNICAL DATA

SURFACE TEXTURE

11190 NW 25th Street, Suite 100 MIAMI, FL 33172 www.rocatileusa.com

Wood Emboss

Format: 7"x48" Type: Virgin Vinyl

Colors: SMOKE, HONEY, Thickness: 2.5 mm

MAPLE Wear Layer 20 mil

Standard Result

SURFACE TREATMENT

Diamond Guard / Health Guard

WARRANTY Commercial / Residential 15 year Commercial / Limited Lifetime Residential

INSTALLATION Glue down

BEVELED EDGE No

CLASSIFICATIONASTM F1700Class III Type B

REACTION TO FIRE ASTM E648-06 Class 1

SMOKE DENSITY ASTM E662-06 Pass <450

SLIP RESISTANCE ASTM C1028 Pass ADA Compliant (>0.50)

STAINING RESISTANCE ASTM F925 Pass

LIGHT RESISTANCE ASTM F1514 Pass

ABRASION RESISTANCE ASTM D4060 Pass

DIMENSIONAL STABILITY

ASTM F2199

Pass 0.011 in / ft <0.020 in / ft

ACOUSTIC IMPACT NOISE REDUCTION ASTM E2179-09 ASTM E492-09 ΔIIC = 4 dB

STATIC LOAD ASTM F970 Pass 1000 psi / 250 psi (<0.005 in)

FLEXIBILITY ASTM F137 Pass

PHTHALATE FREE Yes





