




**Roca**

**Onyx**





**12"x24" R**   **24"x48" R**  
30x60 cm   60x120 cm

## White



**12"x24" R PO**  
GFWHONX-1224PO



**12"x24" R UP**  
GFWHONX-1224



**24"x48" R PO**  
GFWHONX-2448PO

## Technical Specifications

CHARACTERISTICS	STANDARD	DECLARED ASTM	
		Polished	Unpolished
Water Absorption	C373	<=0.5%	<=0.5%
Break Strength	C648	Min. 290	Min. 290
Scratch Hardness	MOH's Scale	3	5
Chemical Resistance	C650	Unaffected	Unaffected
Frost Resistance	C1026	Resistant	Resistant
Group	See FAQ's	3	3
Deep Abrasion - Unglazed Tiles	C1243	Pass	Pass
PEI - Glazed Tiles	C1027	3	3
Minimum Bond Strength (PSI)	C482	165	165
Dynamic Coefficient of Friction (DCOF)	A137.1	>=0.42	<=0.42
Shade and Texture Rating	CTDA "V"	V3	V3
Facial Dimensions	C499	Pass	Pass
Range of Thickness	C499	Pass	Pass
Warping	C485	Pass	Pass
Wedging	C502	Pass	Pass

## Packaging Info

Size	SF per carton	PC per carton
12"x24"	15.50	8
24"x48"	15.50	2