



Calacatta

DUNE
UNIQUE MATTERS

Roca



PORCELAIN

Calacatta

Calacatta, a range of white marble products with grayish veins that will make any space a stylish and appealing setting. Discover our new superwhite floor tile models that come in a polished or brushed finish, with a whiter appearance that is suitable for any room.

Calacatta Bella Satin 23.6"x23.6"

Calacatta

Glazed Porcelain

9mm 23.6"x23.6" 60x60 cm



Bella Satin

23.6"x23.6" 188229

Technical Specifications (Bella Satin)

CHARACTERISTICS	STANDARD	DECLARED ASTM
Dimensions	ISO 10545-2	± 0.6%
Water Absorption	ISO 10545-3	E<=0.5%
Resistance to Surface Abrasion	ISO 10545-7	Class 4
Chemical Resistance	ISO 10545-13	GA
Flatness	ISO 10545-2	± 0.5%
Crazing Resistance	ISO 10545-11	Accomplish
Resistance to Stains	ISO 10545-14	5
Chemical Resistance Swimmingpool	ISO 10545-13	GA
Slip Resistance	41901 EX	Class 0
Breaking Strength	ISO 10545-4:9	>=350 lbf
Frost Resistance	ISO 10545-12	Accomplish
Resistance to Thermal Shock	ISO 10545-9	Accomplish



Carina Satin

23.6"x23.6" 188230

Technical Specifications (Carina Satin)

CHARACTERISTICS	STANDARD	DECLARED ASTM
Dimensions	ISO 10545-2	± 0.6%
Water Absorption	ISO 10545-3	E<=0.5%
Resistance to Surface Abrasion	ISO 10545-7	Class 3
Chemical Resistance	ISO 10545-13	GA
Flatness	ISO 10545-2	± 0.5%
Crazing Resistance	ISO 10545-11	Accomplish
Resistance to Stains	ISO 10545-14	5
Chemical Resistance Swimmingpool	ISO 10545-13	GA
Slip Resistance	41901 EX	Class 0
Breaking Strength	ISO 10545-4:9	>=350 lbf
Frost Resistance	ISO 10545-12	Accomplish
Resistance to Thermal Shock	ISO 10545-9	Accomplish

Packaging Info

Size	SF per carton	PC per carton	BX per pallet
23.6"x23.6"	29.93	2	36

Calacatta

Glazed Porcelain

 11mm



11.8"x35.4"

30x90 cm



Marmolissima

11.8"x35.4"

187589N

Technical Specifications

CHARACTERISTICS	STANDARD	DECLARED ASTM
Dimensions	ISO 10545-2	± 0.5%
Water Absorption	ISO 10545-3	E>10%
Chemical Resistance	ISO 10545-13	GLA
Flatness	ISO 10545-2	± 0.5%
Crazing Resistance	ISO 10545-11	Accomplish
Resistance to Stains	ISO 10545-14	5
Chemical Resistance Swimmingpool	ISO 10545-13	GA
Breaking Strength	ISO 10545-4:9	>=125 lbf
Frost Resistance	ISO 10545-12	N/A
Resistance to Thermal Shock	ISO 10545-9	Accomplish

Packaging Info

Size	SF per carton	PC per carton	BX per pallet
11.8"x35.4"	39.83	4	22