

BIANCO VENATINO PO

TECHNICAL DATA



Format:	All formats available		Type:	Glazed Polished Porcelain	
Color:	All colors		Thickness:	7.0 mm (35X35, 24X48) 8.0 mm (24X24) 8.5 mm(12X24)	
Graphic:	24 (12X24) 12 (24x24)	6 (24x48) 4 (35x35)			
		ASTM Test	ISO Test	Value Required ANSI	Declared ASTM
WATER ABSORPTION		C373	ISO.10545/3	≤0.5%	≤0.5%
BREAKING STRENGHT		C648	ISO.10545/4	≥ 350	≥ 350
SCRATCH HARDNESS		MOH’s Scale	EN-101	-	3
CHEMICAL RESISTANCE		C650	ISO-10545/13	Unaffected	Unaffected
FROST RESISTANCE		C1026	ISO-10545/12	Resistant	Resistant
GROUP		SEE FAQS	SEE FAQS	-	4
PEI - GLAZED TILES		C1027	ISO-10545/7	-	IV
MINIMUM BOND STRENGHT (PSI)		C482	-	≥50 psi	165
DYNAMIC COEFFICIENT OF FRICTION (DCOF)		A137.1	-	≥0.42	<0.40
SHADE AND TEXTURE RATING		CTDA “V”	-	-	V3
FACIAL DIMENSIONS		C499	ISO-10545/2	1.5% Max	Pass
RANGE OF THICKNESS		C499	ISO-10545/2	0.040 Max	Pass
WARPAGE		C485	ISO-10545/2	0.75%	Pass
WEDGING		C502	ISO-10545/2	1.0% Max	Pass

Signature:
Marketing and Product Department



Release Date
09 / 28 / 2023