

BIANCO VENATINO UP

TECHNICAL DATA



Format:	All formats available		Type:	Glazed Porcelain	
Color:	All colors		Thickness:	7.0 mm (35X35, 24X48) 8.0 mm (24X24) 8.5 mm(12X24)	
Graphic:	24 (12X24) 12 (24x24)	6 (24x48) 4 (35x35)			
			ASTM Test	ISO Test	Value Required ANSI
WATER ABSORPTION			C373	ISO.10545/3	≤0.5%
BREAKING STRENGHT			C648	ISO.10545/4	≥ 350
SCRATCH HARDNESS			MOH’s Scale	EN-101	-
CHEMICAL RESISTANCE			C650	ISO-10545/13	Unaffected
FROST RESISTANCE			C1026	ISO-10545/12	Resistant
GROUP			SEE FAQS	SEE FAQS	-
PEI - GLAZED TILES			C1027	ISO-10545/7	-
MINIMUM BOND STRENGHT (PSI)			C482	-	≥50 psi
DYNAMIC COEFFICIENT OF FRICTION (DCOF)			A137.1	-	≥0.42
SHADE AND TEXTURE RATING			CTDA “V”	-	-
FACIAL DIMENSIONS			C499	ISO-10545/2	1.5% Max
RANGE OF THICKNESS			C499	ISO-10545/2	0.040 Max
WARPAGE			C485	ISO-10545/2	0.75%
WEDGING			C502	ISO-10545/2	1.0% Max

Signature:
Marketing and Product Department



Release Date
09 / 28 / 2023