



Selene

DUNE
UNIQUE MATTERS

Roca

Selene

Selene, the new ceramic collection where the natural onyx visual effect is subtly created in a carefully selected array of colors. A modern yet timeless collection, with a wide variety of accessories, to create spaces that are full of character and class.



Selene Grey



Selene Light Satin 35.4"x35.4"



Selene Mariana 11.8"x35.4"



Selene Sky 11.8"x35.4"

Selene

Ceramic Wall & Glazed Porcelain

11mm  **11.8"x35.4"**
30x90 cm



Mariana



11.8"x35.4"
187991

Technical Specifications

CHARACTERISTICS	STANDARD	DECLARED ASTM
Dimensions	ISO 10545-2	± 0.6%
Water Absorption	ISO 10545-3	E>10%
Flatness	ISO 10545-2	± 0.5%
Crazing Resistance	ISO 10545-11	Accomplish
Resistance to Stains	ISO 10545-14	5
Breaking Strength	ISO 10545-4:9	>=125 lbf
Frost Resistance	ISO 10545-12	N/A
Resistance to Thermal Shock	ISO 10545-9	Accomplish



Selene Mariana 11.8"x35.4"

Packaging Info

Size	SF per carton	PC per carton	BX per pallet
11.8"x35.4"	39.83	4	22


Selene

Ceramic Wall & Glazed Porcelain

10mm  **35.4"x35.4"**
90x90 cm



Cappuccino



35.4"x35.4"
188205

Technical Specifications

CHARACTERISTICS	STANDARD	DECLARED ASTM
Dimensions	ISO 10545-2	± 0.6%
Water Absorption	ISO 10545-3	E<=0.5%
Resistance to Surface Abrasion	ISO 10545-7	Class 3
Flatness	ISO 10545-2	± 0.5%
Crazing Resistance	ISO 10545-11	Accomplish
Resistance to Stains	ISO 10545-14	5
Chemical Resistance Swimmingpool	ISO 10545-13	GHB
Slip Resistance	41901 EX	Class 0
Breaking Strength	ISO 10545-4:9	>=350 lbf
Frost Resistance	ISO 10545-12	Accomplish
Resistance to Thermal Shock	ISO 10545-9	Accomplish



Selene Cappuccino 35.4"x35.4"

Packaging Info

Size	SF per carton	PC per carton	BX per pallet
35.4"x35.4"	13.35	1	80


Selene

Ceramic Wall & Glazed Porcelain

10mm  **35.4"x35.4"**
90x90 cm



Grey



35.4"x35.4"
188739

Technical Specifications

CHARACTERISTICS	STANDARD	DECLARED ASTM
Dimensions	ISO 10545-2	± 0.6%
Water Absorption	ISO 10545-3	E≤0.5%
Resistance to Surface Abrasion	ISO 10545-7	Class 3
Chemical Resistance	ISO 10545-13	GHB
Flatness	ISO 10545-2	± 0.5%
Crazing Resistance	ISO 10545-11	Accomplish
Resistance to Stains	ISO 10545-14	5
Slip Resistance	41901 EX	Class 0
Breaking Strength	ISO 10545-4:9	≥350 lbf
Frost Resistance	ISO 10545-12	Accomplish
Resistance to Thermal Shock	ISO 10545-9	Accomplish

Packaging Info

Size	SF per carton	PC per carton	BX per pallet
35.4"x35.4"	13.35	1	80



Selene Grey 35.4"x35.4"


Selene

Ceramic Wall & Glazed Porcelain

10mm  **35.4"x35.4"**
90x90 cm



Dark



35.4"x35.4"
187972

Technical Specifications

CHARACTERISTICS	STANDARD	DECLARED ASTM
Dimensions	ISO 10545-2	± 0.6%
Water Absorption	ISO 10545-3	E<=0.5%
Resistance to Surface Abrasion	ISO 10545-7	Class 2
Chemical Resistance	ISO 10545-13	GHB
Flatness	ISO 10545-2	± 0.5%
Crazing Resistance	ISO 10545-11	Accomplish
Resistance to Stains	ISO 10545-14	5
Slip Resistance	41901 EX	Class 0
Breaking Strength	ISO 10545-4:9	>=350 lbf
Frost Resistance	ISO 10545-12	Accomplish
Resistance to Thermal Shock	ISO 10545-9	Accomplish

Packaging Info

Size	SF per carton	PC per carton	BX per pallet
35.4"x35.4"	13.35	1	80



Selene Dark 35.4"x35.4"


Selene

Ceramic Wall & Glazed Porcelain

9mm  **23.6"x23.6"**
60x60 cm



Sky



23.6"x23.6"
187954

Technical Specifications

CHARACTERISTICS	STANDARD	DECLARED ASTM
Dimensions	ISO 10545-2	± 0.6%
Water Absorption	ISO 10545-3	E<=0.5%
Resistance to Surface Abrasion	ISO 10545-7	Class 4
Chemical Resistance	ISO 10545-13	GA
Flatness	ISO 10545-2	± 0.5%
Crazing Resistance	ISO 10545-11	Accomplish
Resistance to Stains	ISO 10545-14	5
Slip Resistance	41901 EX	Class 0
Breaking Strength	ISO 10545-4:9	>=350 lbf
Frost Resistance	ISO 10545-12	Accomplish
Resistance to Thermal Shock	ISO 10545-9	Accomplish

Packaging Info

Size	SF per carton	PC per carton	BX per pallet
23.6"x23.6"	29.92	3	48



Selene Sky 23.6"x23.6"

Selene

Ceramic Wall & Glazed Porcelain

11mm  **11.8"x35.4"**
30x90 cm



Sky



11.8"x35.4"
187950

Technical Specifications - 11.8"x35.4"

CHARACTERISTICS	STANDARD	DECLARED ASTM
Dimensions	ISO 10545-2	± 0.5%
Water Absorption	ISO 10545-3	E>10%
Chemical Resistance	ISO 10545-13	GA
Flatness	ISO 10545-2	± 0.5%
Crazing Resistance	ISO 10545-11	Accomplish
Resistance to Stains	ISO 10545-14	5
Frost Resistance	ISO 10545-12	N/A
Resistance to Thermal Shock	ISO 10545-9	Accomplish



Selene Sky 11.8"x35.4"

Packaging Info

Size	SF per carton	PC per carton	BX per pallet
11.8"x35.4"	38.83	4	48


Selene

Ceramic Wall & Glazed Porcelain

10mm  **35.4"x35.4"**
90x90 cm



Light



35.4"x35.4"
187971

Technical Specifications

CHARACTERISTICS	STANDARD	DECLARED ASTM
Dimensions	ISO 10545-2	± 0.6%
Water Absorption	ISO 10545-3	E≤0.5%
Resistance to Surface Abrasion	ISO 10545-7	Class 4
Chemical Resistance	ISO 10545-13	GHB
Flatness	ISO 10545-2	± 0.5%
Crazing Resistance	ISO 10545-11	Accomplish
Resistance to Stains	ISO 10545-14	5
Slip Resistance	41901 EX	Class 0
Breaking Strength	ISO 10545-4:9	≥350 lbf
Frost Resistance	ISO 10545-12	Accomplish
Resistance to Thermal Shock	ISO 10545-9	Accomplish

Packaging Info

Size	SF per carton	PC per carton	BX per pallet
35.4"x35.4"	13.35	1	80



Selene Light 35.4"x35.4"

Selene

Ceramic Wall & Glazed Porcelain

11mm  **11.8"x35.4"**
30x90 cm



Light



11.8"x35.4"
187949

Technical Specifications

CHARACTERISTICS	STANDARD	DECLARED ASTM
Dimensions	ISO 10545-2	± 0.5%
Water Absorption	ISO 10545-3	E>10%
Chemical Resistance	ISO 10545-13	GA
Flatness	ISO 10545-2	± 0.5%
Crazing Resistance	ISO 10545-11	Accomplish
Resistance to Stains	ISO 10545-14	5
Breaking Strength	ISO 10545-4:9	>=125 lbf
Frost Resistance	ISO 10545-12	N/A
Resistance to Thermal Shock	ISO 10545-9	Accomplish



Selene Light 11.8"x35.4"

Packaging Info

Size	SF per carton	PC per carton	BX per pallet
11.8"x35.4"	39.83	4	48


Selene

Ceramic Wall & Glazed Porcelain

9mm  **23.6"x23.6"**
60x60 cm



Light Satin



23.6"x23.6"
187953

Technical Specifications

CHARACTERISTICS	STANDARD	DECLARED ASTM
Dimensions	ISO 10545-2	± 0.6%
Water Absorption	ISO 10545-3	E<=0.5%
Resistance to Surface Abrasion	ISO 10545-7	Class 5
Chemical Resistance	ISO 10545-13	GA
Flatness	ISO 10545-2	± 0.5%
Crazing Resistance	ISO 10545-11	Accomplish
Resistance to Stains	ISO 10545-14	5
Slip Resistance	41901 EX	Class 0
Breaking Strength	ISO 10545-4:9	>=350 lbf
Frost Resistance	ISO 10545-12	Accomplish
Resistance to Thermal Shock	ISO 10545-9	Accomplish



Selene Satin

Packaging Info

Size	SF per carton	PC per carton	BX per pallet
23.6"x23.6"	29.92	3	48


Selene

Ceramic Wall & Glazed Porcelain

10mm  **35.4"x35.4"**
90x90 cm



Light Satin



35.4"x35.4"
188311

Technical Specifications

CHARACTERISTICS	STANDARD	DECLARED ASTM
Dimensions	ISO 10545-2	± 0.6%
Water Absorption	ISO 10545-3	E≤0.5%
Resistance to Surface Abrasion	ISO 10545-7	Class 4
Flatness	ISO 10545-2	± 0.5%
Crazing Resistance	ISO 10545-11	Accomplish
Resistance to Stains	ISO 10545-14	5
Slip Resistance	41901 EX	Class 0
Breaking Strength	ISO 10545-4:9	≥350 lbf
Frost Resistance	ISO 10545-12	Accomplish
Resistance to Thermal Shock	ISO 10545-9	Accomplish



Selene Light Satin 35.4"x35.4"

Packaging Info

Size	SF per carton	PC per carton	BX per pallet
35.4"x35.4"	13.35	1	80