

11190 NW 25th Street, Suite 100 MIAMI, FL 33172 www.rocatileusa.com

BAR TILE

TECHNICAL DATA

Format:	3″ X 12″	Туре:	Ceramic W	Ceramic Wall Tile	
Colors:	All Colors Available	Thickness:	7,3 mm	7,3 mm	
Number of faces:	6	Recycled Content: 25% *Pre-		Consumer	
		·			
	ASTM Test	ISO Test	Value Required ANSI	Declared ASTM	
WATER ABSORPTION	C373	ISO.10545/3	<7.0% < wa ≤20%	≤20%	
BREAKING STRENGTH	C648	ISO.10545/4	≥ 125	Not Applicable	
SCRATCH HARDNESS	MOH's Scale	EN-101	_	Not Applicable	
CHEMICAL RESISTANCE	C650	ISO-10545/13	Unaffected	Unaffected	
SHADE AND TEXTURE RATIN	IG CTDA "V"	_	_	V3	

WARPAGE	C485	ISO-10545/2	0.75%	Pass
WEDGING	C502	ISO-10545/2	1.0% Max	Pass

*Contains a percentage of pre-consumer recycled content superior to 25% which has been certified by Bureau Veritas.

Signature: Marketing and Product Department MARKETING: PRODUCT DEPT 11190 NW 25th Street, Suite 100 MIAMI, FL 33172 www.rocatileusa.com

Release Date 10 / 24 / 2022