



11190 NW 25th Street, Suite 100  
MIAMI, FL 33172  
www.rocatileusa.com

# STATUARY WALL

## TECHNICAL DATA

| Format:                  | All formats available             | Type:             | Ceramic wall tile                                    |                |
|--------------------------|-----------------------------------|-------------------|--|----------------|
| Colors:                  | White                             | Thickness:        | 7.0 mm (3x6)<br>7.3 mm (4x10, 3x12)<br>8.0 mm (6x18) |                |
| Number of faces:         | 40 (3X12, 4x10, 3x6)<br>30 (6X18) | Recycled Content: | 25% *Pre -Consumer                                   |                |
|                          | ASTM Test                         | ISO Test          | Value Required ANSI                                  | Declared ASTM  |
| WATER ABSORPTION         | C373                              | ISO.10545/3       | <7.0% < wa ≤20%                                      | ≤20%           |
| BREAKING STRENGTH        | C648                              | ISO.10545/4       | ≥ 125  | Not Applicable |
| SCRATCH HARDNESS         | MOH's Scale                       | EN-101            | -  | Not Applicable |
| CHEMICAL RESISTANCE      | C650                              | ISO-10545/13      | Unaffected   | Unaffected     |
| SHADE AND TEXTURE RATING | CTDA "V"                          | -                 | -  | V2             |
| WARPAGE                  | C485                              | ISO-10545/2       | 0.75%  | Pass           |
| WEDGING                  | C502                              | ISO-10545/2       | 1.0% Max   | Pass           |

\*Contains a percentage of pre-consumer recycled content superior to 25% which has been certified by Bureau Veritas.

Signature:  
Marketing and Product Department



Release Date  
12 / 29 / 2023