

Fume Rigid Core - 12mil

TECHNICAL DATA

11190 NW 25th Street, Suite 100 MIAMI, FL 33172 www.rocatileusa.com

| Format: | 7"x48" | Туре: | SPC |
|-------------------|-------------------------|-------------|---------------------------------------------------|
| Colors: | TOBACCO, CANELA, HONEY, | Thickness: | 4.5 mm |
| | COTTON, SILK, MAPLE | Wear Layer | 12 mil |
| | Standard | | Result |
| SURFACE TREATMENT | | | Nano Silver Coating |
| SURFACE TEXTURE | | | Wood Emboss |
| PADDING | | | 1mm IXPE |
| WARRANTY | Commercial / | Residential | 10 year Commercial / Limited Lifetime Residential |
| INSTALLATION | | | Unilin Click |
| BEVELED EDGE | | | No |
| SMOKE DENSITY | ASTM E6 | 62-19 | Pass <450 |

| SLIP RESISTANCE | ASTM C1028-07e1 | Pass |
|-------------------------------------|-----------------|-------------------------------------------|
| STAINING RESISTANCE | ASTM F925 | Pass |
| LIGHT RESISTANCE | ASTM F1515 | Pass |
| ABRASION RESISTANCE | ASTM D4060 | Pass |
| DIMENSIONAL STABILITY | ASTM F2199 | Pass |
| ACOUSTIC IMPACT NOISE REDUCTION IIC | ASTM E492-14 | IIC = 62 dB concrete slab 6" drop ceiling |
| CALCULATED SOUND TRANMISSION STC | ASTM E413-16 | STC = 68 db |
| STATIC LOAD | ASTM F970-17 | Pass |
| INDENTATION | ASTM F1914 | Pass |

PHTHALATE FREE

Yes



Signature: Marketing and Product Department



Release 05 / 01 / 2024