

Iris Rigid Core - 20mil

TECHNICAL DATA

EVO LUX[®]
LUXURY EVOLVING

11190 NW 25th Street, Suite 100
MIAMI, FL 33172
www.rocatileusa.com

Format:	7"x48"	Type:	SPC
Colors:	SMOKE, OIL, BLEACHED, MAPLE, OFF WHITE, OAK, BLONDE, ALMOND, WALNUT	Thickness:	5.0 mm
		Wear Layer	20 mil

	Standard	Result
--	----------	--------

SURFACE TREATMENT		Nano Silver Coating
SURFACE TEXTURE		Wood Emboss
PADDING		1mm IXPE
WARRANTY	Commercial / Residential	15 year Commercial / Limited Lifetime Residential
INSTALLATION		Unilin Click
BEVELED EDGE		No
SMOKE DENSITY	ASTM E662-19	Pass <450
STATIC COEFFICIENT OF FRICTION	ASTM C1028-07e1	Pass
CHEMICAL RESISTANCE	ASTM F925	Pass
RESISTANCE TO LIGHT	ASTM F1515	Pass
ABRASION RESISTANCE	ASTM D4060	Pass
DIMENSIONAL STABILITY	ASTM F2199	Pass
ACOUSTIC IMPACT NOISE REDUCTION IIC	ASTM E492-14	IIC = 62 dB 6" concrete slab drop ceiling
CALCULATED SOUND TRANSMISSION STC	ASTM E413-16	STC = 68 db
STATIC LOAD	ASTM F970	Pass
INDENTATION	ASTM F1914	Pass
PHthalate FREE		Yes



Signature:
Marketing and Product Department

Roca
MARKETING & PRODUCT DEPT
11190 NW 25th Street, Suite 100
MIAMI, FL 33172
www.rocatileusa.com

Release
05 / 01 / 2024