

Lotus 12mil Glue Down

TECHNICAL DATA

BEVELED EDGE

ABRASION RESISTANCE

DIMENSIONAL STABILITY

ACOUSTIC IMPACT NOISE REDUCTION

11190 NW 25th Street, Suite 100 MIAMI, FL 33172 www.rocatileusa.com

No

Pass

Pass 0.011 in / ft < 0.020 in / ft

 Δ IIC = 4 dB

Yes

Format: 7"x48" Type: Virgin Vinyl

Colors: BLONDE, MAPLE, ASH, Thickness: 2.0 mm

SNOW, TAUPE, COCOA. Wear Layer 12 mil

Standard Result

SURFACE TREATMENT

Diamond Guard / Health Guard

SURFACE TEXTURE Wood Emboss

WARRANTY Commercial / Residential 10 year Light Commercial / Limited Lifetime Residential

INSTALLATION Glue down

CLASSIFICATION ASTM F1700 Class III Type B

REACTION TO FIRE ASTM E648-06 Class 1

SMOKE DENSITY ASTM E662-06 Pass <450

SLIP RESISTANCE ASTM C1028 Pass ADA Compliant (>0.50)

STAINING RESISTANCE ASTM F925 Pass

LIGHT RESISTANCE ASTM F1514 Pass

ASTM D4060

ASTM F2199

ASTM E2179-09 ASTM E492-09

STATIC LOAD ASTM F970 Pass 1000 psi / 250 psi (<0.005 in)

FLEXIBILITYASTM F137Pass

floor

PHTHALATE FREE



