

Powell 20mil Glue Down

TECHNICAL DATA

Format:	7"x48"	Type:	PVC
Colors:	RIDGE, OREGON, SILVER, WEATH, OAK, DRIFTWOOD	Thickness:	2.5 mm
		Wear Layer	20 mil

	Standard	Result
--	----------	--------

SURFACE TREATMENT		Nano Silver Coating
SURFACE TEXTURE		Wood Emboss
WARRANTY	Commercial / Residential	15 year Commercial / Limited Lifetime Residential
INSTALLATION		Glue down
BEVELED EDGE		No
CLASSIFICATION	ASTM F1700	Class III Type B
REACTION TO FIRE	ASTM E648-06	Class 1
SMOKE DENSITY	ASTM E662-06	Pass <450
COEFFICIENT OF FRICTION	ASTM C1028	Pass ADA Compliant (.0.50)
STAINING RESISTANCE	ASTM F925	Pass
LIGHT RESISTANCE	ASTM F1515	Pass
ABRASION RESISTANCE	ASTM D4060	Pass
DIMENSIONAL STABILITY	ASTM F2199	Pass
ACOUSTIC IMPACT NOISE REDUCTION	ASTM E2179-09 ASTM E492-09	Δ IIC = 4 dB
STATIC LOAD	ASTM F970	Pass
FLEXIBILITY	ASTM F137	Pass
PHthalate FREE		Yes



Signature:
Marketing and Product Department