



**Pietrasanta**

**DUNE**  
UNIQUE MATTERS

**Roca**

# Pietrasanta

Tradition and history blend to create the new Pietrasanta collection, inspired by the genuine Cardoso stone. The richness of this tiles collection is, undoubtedly, its graphic and chromatic variety, produced by a careful selection of Cardoso stone blocks with very different tonalities and grains.



Pietrasanta Light Grey 35"x35"



Pietrasanta Ivory 35"x35" Anti-Slip



Pietrasanta Light Grey 35"x35" / Pietrasanta Light Grey 3"x11"



Pierasanta 35"x35" PO / Pietrasanta Light Grey 3"x11"

# Pietrasanta

Glazed Porcelain



35"x35"  
90x90 cm

3"x11"  
7x28 cm




**Ivory**



35"x35" PO  
188803

35"x35" Anti-Slip  
188801



**Light Grey**



35"x35" PO  
188804

35"x35" Anti-Slip  
188802

## Technical Specifications 6"x6" PO

CHARACTERISTICS	STANDARD	DECLARED ASTM
Dimensions	ISO-10545-2	± 0.6%
Water Absorption	ISO-10545-3	E<=0.5%
Resistance to Surface Abrasion	ISO-10545-7	Class 4
Chemical Resistance	ISO-10545-13	GLA
Flatness	ISO-10545-2	± 0.5%
Resistance to Stains	ISO-10545-14	5
Breaking Strength	ISO-10545-4:9	>=350 lbf
Resistance to Thermal Shock	ISO-10545-9	Accomplish
Slip Resistance	DIN 51130	R10

## Technical Specifications 6"x6" Matte Antislip

CHARACTERISTICS	STANDARD	DECLARED ASTM
Dimensions	ISO-10545-2	± 0.6%
Water Absorption	ISO-10545-3	E<=0.5%
Resistance to Surface Abrasion	ISO-10545-7	Class 4
Chemical Resistance Swimming Pool	ISO-10545-13	GHB
Flatness	ISO-10545-2	± 0.5%
Resistance to Stains	ISO-10545-14	5
Breaking Strength	ISO-10545-4:9	>=350 lbf
Resistance to Thermal Shock	ISO-10545-9	Accomplish
Slip Resistance	DIN 51130	R11

## Packaging Info

Size	SF per carton	PC per carton	BX per pallet
6"x6" PO	1.24	1	80
6"x6" Matte Antislip	1.24	1	80



Pietrasanta 35"x35" PO

# Pietrasanta

Glazed Porcelain



35"x35"  
90x90 cm

3"x11"  
7x28 cm



**Ivory**



3"x11"  
188830



**Light Grey**



3"x11"  
188831

## Technical Specifications

CHARACTERISTICS	STANDARD	DECLARED ASTM
Dimensions	ISO-10545-2	± 0.6%
Water Absorption	ISO-10545-3	E<=0.5%
Resistance to Surface Abrasion	ISO-10545-7	Class 4
Chemical Resistance	ISO-10545-13	LA
Flatness	ISO-10545-2	± 0.5%
Resistance to Stains	ISO-10545-14	5
Breaking Strength	ISO-10545-4:9	>=350 lbf
Resistance to Thermal Shock	ISO-10545-9	Accomplish
Slip Resistance	DIN 51130	R10



## Packaging Info

Size	SF per carton	PC per carton	BX per pallet
3"x11"	51.02	26	144