



11190 NW 25th Street, Suite 100  
 MIAMI, FL 33172  
 www.rocatileusa.com

**Model/ Series:** SELVA  
**Size:** All Sizes  
**Colors:** All Colors Available  
**Type:** GRES STONEWARE  
**Application:** INDOOR  
**Thickness:** 8.2mm  
**Recycled Content:** 17% \*Pre-Consumer

**Technical Data**

	ASTM Test	ISO Test	Value Required ANSI	Declared ASTM
Water Absorption	C373	ISO-10545/3	0.5% < wa <= 3.0%	<3%
Break Strength	C648	ISO-10545/4	>= 250	Min. 250
Scratch Hardness	MOH's Scale	EN-101	-	5
Chemical Resistance	C650	ISO-10545/13	Unaffected	Unaffected
Frost Resistance	C1026	ISO-10545/12	Resistant	Resistant
Group	SEE FAQS	SEE FAQS	-	3
Deep Abrasion - Unglazed Tiles	C1243	ISO-10545/6	<175 mm <sup>3</sup>	-
PEI - Glazed Tiles***	C1027	ISO-10545/7	-	4
Minimum Bond Strength (PSI)	C482		>=50 psi	165
Dynamic Coefficient of Friction (DCOF)	A137.1	-	>=0.42	>=0.42
Shade and Texture Rating	CTDA "V"	-	-	V2
Facial Dimensions	C499	ISO-10545/2	1.5% Max	Pass
Range of Thickness	C499	ISO-10545/2	0.040 Max	Pass
Warpage	C485	ISO-10545/2	0.75%	Pass
Wedging	C502	ISO-10545/2	1.0% Max	Pass

0

Signature:  
 Quality Management Manager



Release Date

1/20/2020