



Tile

11190 NW 25th Street, Suite 100  
MIAMI, FL 33172  
www.rocatileusa.com

**Model/ Series:** LIVERPOOL PO

**Size:** All Sizes

**Colors:** All Colors Available

**Type:** GLAZED POLISHED PORCELAIN

**Application:** INDOOR

**Thickness:** 10 mm (24x48), 9mm (24x24), 8.5mm (12x24)

**Number of faces:** 16 (12x24) / 8 (24x24) / 4 (24x48)

**Recycled Content:** 5% \*Pre-Consumer

**Technical Data**

	<b>ASTM Test</b>	<b>ISO Test</b>	<b>Value Required ANSI</b>	<b>Declared ASTM</b>
Water Absorption	C373	ISO-10545/3	<=0.5%	<=0.5%
Break Strength	C648	ISO-10545/4	>= 250	Min. 335
Scratch Hardness	MOH's Scale	EN-101	-	3
Chemical Resistance	C650	ISO-10545/13	Unaffected	Unaffected
Frost Resistance	C1026	ISO-10545/12	Resistant	Resistant
Group	SEE FAQS	SEE FAQS	-	3
Deep Abrasion - Unglazed Tiles	C1243	ISO-10545/6	<175 mm <sup>3</sup>	Pass
PEI - Glazed Tiles***	C1027	ISO-10545/7	-	3
Minimum Bond Strength (PSI)	C482		>=50 psi	165
Dynamic Coefficient of Friction (DCOF)	A137.1	-	>=0.42	<=0.40
Shade and Texture Rating	CTDA "V"	-	-	V3
Facial Dimensions	C499	ISO-10545/2	1.5% Max	Pass
Range of Thickness	C499	ISO-10545/2	0.040 Max	Pass
Warpage	C485	ISO-10545/2	0.75%	Pass
Wedging	C502	ISO-10545/2	1.0% Max	Pass

0

**Signature:**  
Quality Management Manager



**Release Date**

4/6/2020