

11190 NW 25th Street, Suite 100 MIAMI, FL 33172 www.rocatileusa.com

## Model/ Series:

Application:

Number of faces:

**Recycled Content:** 

Thickness:

Size:

**Colors:** 

Type:

## BORNEO

All Sizes All Colors Available COLORED BODY PORCELAIN INDOOR/ OUTDOOR 8.7 mm 30 50% \*Pre-Consumer

<u>Technical Data</u>	ASTM	ISO	Value Required	Declared
	Test	Test	ANSI	ASTM
Water Absorption	C373	ISO-10545/3	<=0.5%	<=0.5%
Break Strength	C648	ISO-10545/4	>= 250	Min. 450
Scratch Hardness	MOH's Scale	EN-101	-	7
Chemical Resistance	C650	ISO-10545/13	Unaffected	Unaffected
Frost Resistance	C1026	ISO-10545/12	Resistant	Resistant
Group	SEE FAQS	SEE FAQS	-	4
Deep Abrasion - Unglazed Tiles	C1243	ISO-10545/6	<175 mm3	Pass
PEI - Glazed Tiles***	C1027	ISO-10545/7	-	-
Minimum Bond Strength (PSI)	C482		>=50 psi	165
Dynamic Coefficient of Friction (DCOF)	A137.1	-	>=0.42	=0.42
Shade and Texture Rating	CTDA "V"	-	-	V3
Facial Dimensions	C499	ISO-10545/2	1.5% Max	Pass
Range of Thickness	C499	ISO-10545/2	0.040 Max	Pass
Warpage	C485	ISO-10545/2	0.75%	Pass
Wedging	C502	ISO-10545/2	1.0% Max	Pass

\*\*\*Contains a percentage of pre-consumer recycled content superior to 80% which has been certified by Bureau Veritas.

**Signature:** Quality Management Manager



**Release Date** 

3/26/2020