



Fabric Grafito 24"x24"

FABRIC & TWEED

Colored Body Porcelain

Roca



Fabric Blanco
24"x48" R
FCWT654011



Fabric Blanco
24"x24" R
FCWT660011



Fabric Blanco
12"x10" Mosaic
FCWT6HO011



Fabric Blanco
8"x48" R
FCWT6FP011



Fabric Blanco
12"x24" R
FCWT657011



Fabric Arena
24"x48" R
FCWT654371



Fabric Arena
24"x24" R
FCWT660371



Fabric Arena
12"x10" Mosaic
FCWT6HO371



Fabric Arena
8"x48" R
FCWT6FP371



Fabric Arena
12"x24" R
FCWT657371



Fabric Gris
24"x48" R
FCWT654021



Fabric Gris
24"x24" R
FCWT660021



Fabric Gris
12"x10" Mosaic
FCWT6HO021



Fabric Gris
8"x48" R
FCWT6FP021



Fabric Gris
12"x24" R
FCWT657021



Fabric Grafito
24"x48" R
FCWT654101



Fabric Grafito
24"x24" R
FCWT660101



Fabric Grafito
12"x10" Mosaic
FCWT6HO101



Fabric Grafito
8"x48" R
FCWT6FP101




Fabric Grafito
12"x24" R
FCWT657101





Tweed Blanco
8"x48" R
FCXT6FP011



Tweed Blanco
12"x24" R
FCXT657011



Tweed Arena
8"x48" R
FCXT6FP371



Tweed Arena
12"x24" R
FCXT657371



Tweed Gris
8"x48" R
FCXT6FP021



Tweed Gris
12"x24" R
FCXT657021



Tweed Grafito
8"x48" R
FCXT6FP101



Tweed Grafito
12"x24" R
FCXT657101

Technical Specs

Characteristics	Standard	Declared ASTM
Water Absorption	C373	$\leq 0.5\%$
Break Strength	C648	Min. 450
Scratch Hardness	MOH's Scale	5
Chemical Resistance	C650	Unaffected
Frost Resistance	C1026	Resistant
Group	C1027	4
Minimum Bond Strength (PSI)	C482	165
Dynamic Coefficient of Friction (DCOF)	A137.1	≥ 0.50
Shade and Texture Rating	CTDA "V"	V3
Facial Dimensions	C499	Pass
Range of Thickness	C499	Pass
Warpage	C485	Pass
Wedging	C502	Pass

Packaging Info

Size	SF. Per Carton	Pieces Per Carton
24"x48"	23.25	3
8"x48"	10.08	4
24"x24"	11.63	3
12"x24"	13.56	7
12"x10" Mosaic	2.95	6

