



**Roca**

**Pro**





PORCELAIN

# Pro

Basic and essential. This sums up the Pro series, which comes in an array of neutral colors that are practical to use and easy to maintain in any type of space.

Glazed & Polished Porcelain

35"x35" R - 24"x48" R - 24"x24" R - 12"x24" R





Pro Cement 24"x24" R UP




Pro Ivory 24"x24" R UP



## Pro

## Glazed & Polished Porcelain




35"x35"  
90x90 cm

24"x48" R  
60x120 cm

24"x24" R  
60x60 cm

12"x24" R  
30x60 cm

## Ivory



35"x35" R  
UP: I64240064A  
PO: 196080016A



24"x48" R  
UP: I96070222A  
PO: I960500014A




24"x24" R  
UP: I64270020A  
PO: I96070422A



12"x24" R  
UP: I96070122A  
PO: I96070322A

## Nude



35"x35" R  
UP: I64240066A  
PO: 19608001 SA



24"x48" R  
UP: I96070224A  
PO: I960500016A




24"x24" R  
UP: I64270016A  
PO: I96070424A



12"x24" R  
UP: I96070124A  
PO: I96070324A



Sand



35"x35" R  
UP: I64240068A  
PO: I96080020A



24"x48" R  
UP: 196070226A  
PO: 196050010A



24"x24" R  
UP: I6427001SA  
PO: I96070426A



12"x24" R  
UP: I96070126A  
PO: I96070326A



## Cement



35"x35" R  
UP: I64240060A  
PO: 196080012A



24"x48" R  
UP: I96070216A  
PO: I960500012A



24"x24" R  
UP: I64270022A  
PO: 19607041 SA



12"x24" R  
UP: I9607011 SA  
PO: I96070316A



# Pro

Glazed & Polished Porcelain

8.5-10  
mm













35"x35"  
90x90 cm

24"x48" R  
60x120 cm

24"x24" R  
60x60 cm

12"x24" R  
30x60 cm

## Concrete



35"x35" R  
UP: 164240062A  
PO: I96080014A



24"x48" R  
UP: I96070220A  
PO: I96050006A



24"x24" R  
UP: I64270024A  
PO: I96070420A



12"x24" R  
UP: I96070120A  
PO: I96070320A



Pro Concrete 24"x48" R UP



Technical Specifications

| CHARACTERISTICS                        | STANDARD    | DECLARED ASTM |            |
|----------------------------------------|-------------|---------------|------------|
|                                        |             | Polished      | Unpolished |
| Water Absorption                       | C373        | <=0.5%        | <=0.5%     |
| Break Strength                         | C648        | Min. 335      | Min. 335   |
| Scratch Hardness                       | MOH's Scale | 3             | 5          |
| Chemical Resistance                    | C650        | Unaffected    | Unaffected |
| Frost Resistance                       | C1026       | Resistant     | Resistant  |
| Group                                  | See FAQ's   | 3             | 4          |
| Deep Abrasion - Unglazed Tiles         | C1243       | Pass          | Pass       |
| PEI- Glazed Tiles***                   | C1027       | 3             | -          |
| Minimum Bond Strength (PSI)            | C482        | 165           | 165        |
| Dynamic Coefficient of Friction (DCOF) | A137.1      | <=0.40        | >=0.42     |
| Shade and Texture Rating               | CTDA "V"    | V3            | V3         |
| Facial Dimensions                      | C499        | Pass          | Pass       |
| Range of Thickness                     | C499        | Pass          | Pass       |
| Warpage                                | C485        | Pass          | Pass       |
| Wedging                                | C502        | Pass          | Pass       |

Packaging Info

| Size       | SF per carton | PC per carton |
|------------|---------------|---------------|
| 12"x24"    | 18.94         | 10            |
| 24"x24" PO | 19.05         | 5             |
| 24"x24" UP | 23.25         | 6             |
| 35"x35"    | 17.22         | 2             |
| 24"x48"    | 15.28         | 2             |