Roca

Pro Max

Pro Max

Glazed Porcelain

8.5-9* mm | ABS | M | V3

24”x24” R 60x60 cm

12”x24” R 30x60 cm

Ivory

12"x24" R UP
I64270134A

24"x24" R UP
I64270034A

Cement

12"x24" R UP
I64270136A

12"x24" R ABS
I64260136A

24"x24" R UP
I64270036A

Nude

12"x24" R UP
I64270130A

12"x24" R ABS
I64260130A

24"x24" R UP
I64270030A

Concrete

12"x24" R UP
I64270138A

12"x24" R ABS
I64260138A

24"x24" R UP
I64270038A

Sand

12"x24" R UP
I64260132A

24"x24" R UP
I64270032A

Pro Max

Glazed Porcelain

Technical Specifications

CHARACTERISTICS	STANDARD	DECLARED ASTM	
		Unpolished	ABS
Water Absorption	C373	<=0.5%	<=0.5%
Break Strength	C648	Min. 335	Min. 335
Scratch Hardness	MOH's Scale	5	8
Chemical Resistance	C650	Unaffected	Unaffected
Frost Resistance	C1026	Resistant	Resistant
Group	See FAQ's	4	5
Deep Abrasion - Unglazed Tiles	C1243	Pass	Pass
PEI- Glazed Tiles***	C1027	-	5
Minimum Bond Strength (PSI)	C482	165	165
Dynamic Coefficient of Friction (DCOF)	A137.1	>=0.42	>=0.42
Shade and Texture Rating	CTDA "V"	V3	V3
Facial Dimensions	C499	Pass	Pass
Range of Thickness	C499	Pass	Pass
Warpage	C485	Pass	Pass
Wedging	C502	Pass	Pass

Packaging Info

Size	SF per carton	PC per carton
12"x24" UP	18.94	10
12"x24" ABS	20.34	10
24"x24" UP	23.25	6