







TECHNICAL INFORMATION

| CHARACTERISTICS                        | STANDARD     | Declared ASTM |
|--|--------------|---------------|
| Water Absorption                       | ISO-10545/3  | <=0.5%        |
| Break Strength                         | ISO-10545/4  | ☒ Lbs         |
| Scratch Hardness                       | EN-101       | ☒             |
| Chemical Resistance                    | ISO-10545/13 | Unaffected    |
| Frost Resistance                       | ISO-10545/12 | Resistant     |
| Group                                  | ISO-10545/7  | 4             |
| Minimum Bond Strength (PSI)            | C482         |               |
| Dynamic Coefficient of Friction (DCOF) | A137.1       | DA☒☒          |
| Shade and Texture Rating               | CTDA         | s☒            |
| Facial Dimensions                      | ISO-10545/2  | Pass          |
| Range of Thickness                     | ISO-10545/2  | Pass          |
| Warpage                                | ISO-10545/2  | Pass          |
| Wedging                                | ISO-10545/2  | Pass          |
| PEI                                    | C1027        | 4             |

Available Sizes



PACKAGING INFORMATION

| SIZE    | SF PER CARTON | PC PER CARTON |
|---------|---------------|---------------|
| 12"x24" |               |               |
| 24"x24" |               |               |
| 24"x48" |               |               |