



**Roca**

**Lassa White**





PORCELAIN

# Lassa White

Lassa White, relaxed and serene beauty, created through the delicate visual interplay of its parallel lines and subtle changes in tone. Its polished finish also brings brightness into designs.

Lassa White 24"x48" R PO & 6"x18" Wall

**Matte & Polished Porcelain + Ceramic Wall**

24"x48 R PO - 24"x48 R UP - 12"x24" R PO -  
12"x24" UP - 6"x18" Wall



## Matte & Polished Porcelain









## White



24"x48" R PO  
FLWPET3A31



12"x24" R PO  
FLWPER5A31



**6"x18" Wall**  
FLWRVW2A31



13"x13" Mosaic  
FLWPPR8A31



6"x18" Bullnose  
FLWRVO4A31



3"x12" Bullnose  
FLWPP64A31

## Technical Specifications - Wall

| CHARACTERISTICS          | STANDARD    | DECLARED ASTM    |
|--------------------------|-------------|------------------|
| Water Absorption         | C373        | >10%             |
| Break Strength           | C648        | Meets or Exceeds |
| Scratch Hardness         | MOH's Scale | N/A              |
| Chemical Resistance      | C650        | Unaffected       |
| Shade and Texture Rating | CTDA "V"    | V2               |
| Warpage                  | C485        | Pass             |
| Wedging                  | C502        | Pass             |

## Technical Specifications - Floor

| CHARACTERISTICS                        | STANDARD    | DECLARED ASTM |            |
|----------------------------------------|-------------|---------------|------------|
|                                        |             | Matte         | Polished   |
| Water Absorption                       | C373        | <=0.5%        | <=0.5%     |
| Break Strength                         | C648        | Min. 335      | Min. 335   |
| Scratch Hardness                       | MOH's Scale | 5             | 3          |
| Chemical Resistance                    | C650        | Unaffected    | Unaffected |
| Frost Resistance                       | C1026       | Resistant     | Resistant  |
| Group                                  | See FAQ's   | 4             | 3          |
| Deep Abrasion - Unglazed Tiles         | C1043       | Pass          | Pass       |
| PEI- Glazed Tiles***                   | C1027       | 4             | 3          |
| Minimum Bond Strength (PSI)            | C482        | 165           | 165        |
| Dynamic Coefficient of Friction (DCOF) | A137.1      | >=0.42        | <=0.40     |
| Shade and Texture Rating               | CTDA "V"    | V2            | V2         |
| Facial Dimensions                      | C499        | Pass          | Pass       |
| Range of Thickness                     | C499        | Pass          | Pass       |
| Warpage                                | C485        | Pass          | Pass       |
| Wedging                                | C502        | Pass          | Pass       |

## Packaging Info

| Size            | SF per carton | PC per carton |
|-----------------|---------------|---------------|
| 12"x24" R PO    | 18.84         | 10            |
| 12"x24" UP      | 20.34         | 10            |
| 24"x48" R       | 15.28         | 2             |
| 13"x13" Mosaic  | 13.13         | 11            |
| 3"x12" Bullnose | 5.92          | 24            |
| 6"x18" Wall     | 11.95         | 16            |
| 6"x18" Bullnose | 11.95         | 16            |