



11190 NW 25th Street, Suite 100
 MIAMI, FL 33172
 www.rocatileusa.com

Model/ Series:

DISTRICT

Size:
Colors:
Type:
Thickness:
Recycled Content:

All Sizes
 All Colors Available
 COLORED BODY PORCELAIN
 9 mm (20"x40" & 40"x40") / 10 mm (24"x24") / 10.5 mm (24"x48")

- *Pre-Consumer

Technical Data

	ASTM Test	ISO Test	Value Required ANSI	Declared ASTM
Water Absorption	C373	ISO-10545/3	<=0.5%	<=0.5%
Break Strength	C648	ISO-10545/4	>= 250	Min. 290
Scratch Hardness	MOH's Scale	EN-101	-	5
Chemical Resistance	C650	ISO-10545/13	Unaffected	Unaffected
Frost Resistance	C1026	ISO-10545/12	Resistant	Resistant
Group	SEE FAQs	SEE FAQs	-	3
Deep Abrasion - Unglazed Tiles	C1243	ISO-10545/6	<175 mm ³	Pass
PEI - Glazed Tiles***	C1027	ISO-10545/7	-	3 & 2*
Minimum Bond Strength (PSI)	C482		>=50 psi	165
Dynamic Coefficient of Friction (DCOF)	A137.1	-	>=0.42	>=0.42
Shade and Texture Rating	CTDA "V"	-	-	V2
Facial Dimensions	C499	ISO-10545/2	1.5% Max	Pass
Range of Thickness	C499	ISO-10545/2	0.040 Max	Pass
Warping	C485	ISO-10545/2	0.75%	Pass
Wedging	C502	ISO-10545/2	1.0% Max	Pass

Signature:
 Quality Management Manager



Release Date 5/27/2020