



11190 NW 25th Street, Suite 100  
MIAMI, FL 33172  
www.rocatileusa.com

**Model/ Series:** STATUARY II PO  
**Size:** All Sizes  
**Colors:** All Colors Available  
**Type:** GLAZED POLISHED PORCELAIN  
**Thickness:** 10 mm (35x35, 24x48), 9mm (24x24), 8.5mm (12x24)  
**Number of faces:** 11 (12x24) / 12 (24x24) / 6 (35x35) / 10 (24x48)  
**Recycled Content:** 5% \*Pre-Consumer

| <b>Technical Data</b>                  | <b>ASTM<br/>Test</b> | <b>ISO<br/>Test</b> | <b>Value Required<br/>ANSI</b> | <b>Declared<br/>ASTM</b> |
|----------------------------------------|----------------------|---------------------|--------------------------------|--------------------------|
| Water Absorption                       | C373                 | ISO-10545/3         | <=0.5%                         | <=0.5%                   |
| Break Strength                         | C648                 | ISO-10545/4         | >= 250                         | Min. 335                 |
| Scratch Hardness                       | MOH's Scale          | EN-101              | -                              | 3                        |
| Chemical Resistance                    | C650                 | ISO-10545/13        | Unaffected                     | Unaffected               |
| Frost Resistance                       | C1026                | ISO-10545/12        | Resistant                      | Resistant                |
| Group                                  | SEE FAQS             | SEE FAQS            | -                              | 3                        |
| Deep Abrasion - Unglazed Tiles         | C1243                | ISO-10545/6         | <175 mm <sup>3</sup>           | Pass                     |
| PEI - Glazed Tiles***                  | C1027                | ISO-10545/7         | -                              | 4                        |
| Minimum Bond Strength (PSI)            | C482                 |                     | >=50 psi                       | 165                      |
| Dynamic Coefficient of Friction (DCOF) | A137.1               | -                   | >=0.42                         | <0.40                    |
| Shade and Texture Rating               | CTDA "V"             | -                   | -                              | V3                       |
| Facial Dimensions                      | C499                 | ISO-10545/2         | 1.5% Max                       | Pass                     |
| Range of Thickness                     | C499                 | ISO-10545/2         | 0.040 Max                      | Pass                     |
| Warpage                                | C485                 | ISO-10545/2         | 0.75%                          | Pass                     |
| Wedging                                | C502                 | ISO-10545/2         | 1.0% Max                       | Pass                     |

0

**Signature:**  
Quality Management Manager



**Release Date** 4/6/2020