



11190 NW 25th Street, Suite 100  
 MIAMI, FL 33172  
 www.rocatileusa.com

**Model/ Series:**

**Size:**  
**Colors:**  
**Type:**  
**Thickness:**  
**Number of faces:**  
**Recycled Content:**

**RATTAN**  
 Natural Mix  
 PORCELAIN TILE  
 9.0 mm  
 1 (24"x24" R)

**Technical Data**

|  | <b>ASTM Test</b> | <b>ISO Test</b> | <b>Value Required ANSI</b> | <b>Declared ASTM</b>          |
|--|------------------|-----------------|----------------------------|-------------------------------|
| Water Absorption                       | C373             | ISO-10545/3     | <=0.5%                     | <=0.5%                        |
| Break Strength                         | C648             | ISO-10545/4     | >=275                      | Min. 275                      |
| Chemical Resistance                    | C650             | ISO-10545/13    | Unaffected                 | CLASS A (Resist) <sup>1</sup> |
| Stain Resistance                       | C1378            | -               | -                          | CLASS A                       |
| Frost Resistance                       | C1026            | ISO-10545/12    | Resistant                  | Resistant                     |
| Thermal Shock Resistance               | C484             | -               | Resistant                  | Resistant                     |
| Crazing Resistance                     | C424             | -               | Resistant                  | Resistant                     |
| Group                                  | SEE FAQS         | SEE FAQS        | -                          | 4                             |
| PEI - Glazed Tiles                     | C1027            | ISO-10545/7     | -                          | IV                            |
| Dynamic Coefficient of Friction (DCOF) | A326.3           | -               | >=0.42                     | >=0.42                        |
| Shade and Texture Rating               | CTDA "V"         | -               | -                          | V3                            |
| Facial Dimensions                      | C499             | ISO-10545/2     | 1.5% Max                   | Pass                          |
| Range of Thickness                     | C499             | ISO-10545/2     | 0.040 Max                  | Pass                          |
| Warpage                                | C485             | ISO-10545/2     | 0.75%                      | Pass                          |
| Wedging                                | C502             | ISO-10545/2     | 1.0% Max                   | Pass                          |

\*\*\*Contains a percentage of pre-consumer recycled content superior to 25% which has been certified by Bureau Veritas.

**Signature:**  
 Quality Management Manager



**Release Date**

6/09/2022